ZANUSSI

ZDT26022FA

Dry Natural. Easy
The new AirDry technology will easily dry your dishes with natural airflows. The dishwasher door opens up 10 cm in the last part of the program so when you are ready to unload your dishes they will be clean and dry. All natural.

•AirDry Technology
•Hygiene Plus
•Fully Integrated
•Auto-Program
•Third Cutlery Tray

Product Benefits & Features

Complete clean in half the time
Use the Time Manager feature to cut the duration of the dishwashing cycle in half. Meaning you can have your dishes cleaned and ready to use when it's convenient.

Choose the most convenient time of day to do dishes
The 24h delay function enables you to postpone the dishwasher cycle for up to 24 hours in one-hour increments. So you can begin the cleaning process when you have the time or energy. It's ideal for taking advantage of off-peak rates or running a programme when hot water isn't required elsewhere

Clean dishes, green conscience
The special sensor in our AutoWash feature detects how much cleaning your dishes need. Using just the right amount of water, energy and detergent to do the job properly. Meaning dishes are cleaned in the most eco-friendly way possible.

- Energy class / Cleaning perf. / Drying perf.: A / A / A
- Glass protection program
- 6 programmes, 4 temperatures
- Drying system: Air Dry Technology
- Text/symbol panel
- Panel with symbols
- Delay start option from 1 to 24 hours
- Remaining time indication
- Water sensor detects the level of dirt and adjusts water consumption
- Indications for salt and rinse aid.
- Height adjustable upper basket, even when fully loaded
- Cutlery basket
- Aquastop System

ZANUSSI

Product Specification

Cleaning Performance	A
Drying Performance	A
Energy consumption Annual (kWh)	0
Declared Program	Economic 50
Number of IEC Place Settings	13
Color	Stainless Steel
Color control panel	Stainless Steel
Door Color	NO
Required Fuse	10
Connected Load	1950
Voltage	220-240
Height (mm)	818
Width (mm)	596
Depth (mm)	550
Product Installation	Built-in

PSGBDW150D002001

596 550
min. 550
820-880
818-878 650
600
150
50
1200
max. 130
Ⓐ 645-720
Ⓑ 645-776

*820
**880
940
Ⓐ
Ⓑ

Ⓐ * 90-175 ** 150-235 210-295
Ⓑ * 40-175 ** 100-235 160-295